

**Model Definition**

Model	Power supply capacity (KVA)	Input current (A)	Output current (A)	Adaptive motor	
				(KW)	(HP)
Three - phase power supply: 380V 50 / 60 Hz					
<b>HV480-R75G3</b>	1.5	3.4	2.1	0.75	1
<b>HV480-1R5G3</b>	3.0	5.0	3.8	1.5	2
<b>HV480-2R2G3</b>	4.0	5.8	5.1	2.2	3
<b>HV480-004G3</b>	5.9	10.5	9.0	4.0	5
<b>HV480-5R5G3</b>	8.9	14.6	13.0	5.5	7.5
<b>HV480-7R5G3</b>	11	20.5	17.0	7.5	10
<b>HV480-011G3</b>	17	26.0	25.0	11	15
<b>HV480-015G3</b>	21	35.0	32.0	15	20
<b>HV480-018G3</b>	45	42	37	18.5	25
<b>HV480-022G3</b>	54	50	45	22	30
<b>HV480-030G3</b>	65	68	60	30	40
<b>HV480-037G3</b>	63	83	75	37	50
<b>HV480-045G3</b>	81	102	91	45	60
<b>HV480-055G3</b>	97	124	112	55	75
<b>HV480-075G3</b>	127	169	150	75	100
<b>HV480-093G3</b>	150	203	176	90	125
<b>HV480-110G3</b>	179	248	210	110	150
<b>HV480-132G3</b>	192	256	253	132	175
<b>HV480-160G3</b>	231	307	304	160	220
<b>HV480-185G3</b>	242	350	340	185	245
<b>HV480-200G3</b>	250	385	377	200	270